

Soft Flex

By The Sea Bracelet

Design by **Sara Oehler**

Size: Made for a 6" wrist.

*Length: Beadwork is about 6",
7 1/4" from clasp end to end.*

Width: Beadwork is about 3/4".

Materials

Soft Touch™ Beading Wire, .010 Very Fine,
Black Color - 10 ft

Soft Flex® Beading Wire, .019 Medium,
Black Onyx Color - 6"

Turquoise Blue Picasso
2.5x5-mm SuperDuos - 212 pcs

2x2mm Sterling Silver
Soft Flex® Crimp Tube - 2 pcs

Starfish Toggle Clasp - 1 set

Tools

Mini Macramé Board

Magical Crimping Pliers

Cutters

Special T Glue

Instructions

Step 1: (Demonstrate) Using 3 inches of medium beading wire, string a crimp tube and a superduo. Pass the wire back through the tube. String the toggle. Crimp the tube, trim excess wire.

Step 2: (Demonstrate) Slide the toggle bar into the top, middle slot on the mini macramé board.

Step 3: (Demonstrate) Row 1: Using 10 feet of very fine beading wire, string a superduo, the second hole in the first superduo in Step 1 and a superduo. Center the wire. (3 total beads)

Step 4: Row 2: On the left, string a superduo, the second hole of the previous row, a superduo, the second hole of the previous row and a superduo. Snug the beads together. Pass the wire on the right back through the same beads in the opposite direction. (6 total beads)

Step 5: Row 3: On the left, string a superduo, the second hole of the previous row, a superduo, the second hole of the previous row, a superduo, the second hole of the previous row and a superduo. Snug the beads together. Pass the wire on the right back through the same beads in the opposite direction. (10 total beads)

Instructions continued on next page.



Resources

Soft Flex Company: www.SoftFlexCompany.com

BeadShop.com: www.BeadShop.com

Green Girl Studios: www.GreenGirlStudios.com

By The Sea Bracelet Instructions Continued

Step 6: Row 4: On the left, string a superduo, the second hole of the previous row, a superduo, the second hole of the previous row, a superduo, the second hole of the previous row, a superduo, the second hole of the previous row and a superduo. Snug the beads together. Pass the wire on the right back through the same beads in the opposite direction. (15 total beads)

Step 7: (Demonstrate) Row 5: On the left, pass the wire through the second hole of the previous row, a superduo, the second hole of the previous row, a superduo, the second hole of the previous row, a superduo, the second hole of the previous row, a superduo and a second hold of the previous row. Pass the wire on the right back through the same beads in the opposite direction. (19 total beads)

Step 8: Row 6-51: Repeat Rows 4-5 for about 5 inches.

Step 9: (Demonstrate) Row 52: After your last repetition of Row 5, on the left, string a hole of the previous row, a superduo bead, a hole of the previous row, a superduo bead and a hole of the previous row. Pass the wire on the right back through the same beads in the opposite direction.

Step 10: Row 53: On the left, string a hole of the previous row and a superduo bead. On the right, string a hold of the previous row.

Step 11: (Demonstrate) Knot the wires together between two superduo beads. Trim excess wire and add a dab of Special T Glue to the knot.

Step 12: Repeat Step 1 to attach the second half of the clasp.

Tips: If you work with a shorter length of wire and need to add more wire, center a new wire in the row where you are leaving off, continue beading with the new wire. After several rows are complete with the new wires, weave the old wires back into the beadwork to knot together between two superduo beads. Trim excess wire and add a dab of Special T Glue to the knot.



Watch Sara Oehler show how to make the **By The Sea Bracelet** on "By The Sea", episode 2701 of **Beads Baubles and Jewels** on your local public television station. This season started on January 24, 2019. Check your local listings for air times.

Projects not intended for children under the age of 13. The information on this instruction sheet is presented in good faith, but no warranty is given, nor results guaranteed. Soft Flex® Company disclaims all liability from any injury to anyone undertaking the construction of this project as a result of improper safety precautions.