

Soft Flex®

Elegant Dangles Earrings

Designed by: **Jamie Hogsett**

Skill Level: **Beginner**

Materials

Elegant Trios™ wire set (Coral, Onyx, Copper)

2mm x 2mm Sterling Silver Crimp Tubes - 4 crimps

22 gauge 2" Copper Head Pins - 2 head pins

Antiqued Copper Ear Wires - 1 pair ear wire

13mm Sterling Silver 3 Hole Round Connector - 2 connectors

4mm Swarovski crystal rounds in Siam - 6 crystals

4mm Swarovski crystal rounds in Crystal Satin - 4 crystals

4mm Swarovski crystal rounds in Crystal Copper - 4 crystals

Tools

Cutters

Bead Crimping Pliers

Round Nose Pliers

Chain Nose Pliers



Instructions

Step 1: Use 1 head pin to string 1 connector, making sure to pass through the center holes of the connector, and 1 Siam crystal. Form a wire wrapped loop that attaches to 1 ear wire. Repeat entire step for the second earring.

Step 2: Cut two 4 1/2" pieces of Copper wire. Cut two 4" pieces of Coral wire. Cut two 3 1/2" pieces of Onyx wire.

Step 3: Pass one end each of 1 Copper wire, 1 Coral wire, and 1 Onyx wire through the bottom left hole of the connector. Use all three wires to string 1 crimp tube. Place the tube at the very end of the wires and crimp. Pull the wires down so that the crimp tube rests just inside the connector.

Step 4: Use the Coral wire to string 1 Crystal Satin crystal, 1 Siam crystal, 1 Crystal Copper crystal, 1 Crystal Satin crystal, 1 Siam crystal, and 1 Crystal Copper crystal.

Step 5: Use all three wires to pass through the bottom right hole of the connector. Use all three wires to string 1 crimp tube. Place the tube at the very end of the wires and crimp. Pull the wires down so that the crimp rests just inside the connector.

Step 6: Repeat Step 3 for the second earring. Repeat Step 4, reversing the stringing sequence (Crystal Copper, Siam, then Crystal Satin). Repeat Step 5 for the second earring.

Projects not intended for children under the age of 13.

The information on this instruction sheet is presented in good faith, but no warranty is given, nor results guaranteed.

Soft Flex® Company disclaims all liability from any injury to anyone undertaking the construction of this project as a result of improper safety precautions.